

Performus™ III & IV Dispensers

EFD[®]
A NORDSON COMPANY

For applications that require a timed shot and vacuum control.

The Performus III features a 0-7 bar (0-100 psi) pressure regulator that handles all fluids.

The Performus IV has a 0-1 bar (0-15 psi) regulator that provides greater control when dispensing thin fluids.



**Performance
Guarantee**

EFD's Performus dispensers increase throughput, improve yields, and reduce production costs through controlled application of adhesives, lubricants and other assembly fluids.

Eight different dispenser configurations provide a cost-effective way to select the exact features needed to improve your specific fluid application process.

Features

- Choice of pressure regulators
- Digital timer
- Timed or steady operation
- Vacuum control keeps thin fluids from dripping
- Digital time/pressure display
- Electric foot pedal

Benefits

- Consistent dots and fills
- Neat beads
- No guesswork or fluid waste
- Less operator fatigue
- Compact design saves space

www.efd-inc.com info@efd-inc.com USA & Canada 800-556-3484 Europe +44 (0) 1582 666334 Asia +86 (21) 5854 2345


Sales and service of EFD dispensing systems are available worldwide.

Performus™ III & IV Dispensers



LED **P** **T** **Performus III & IV**
LED Display, Timer, Vacuum

Each dispenser kit includes:

- (1) adapter assembly 
- (2) boxes of syringe barrels and pistons (same size)
- (2) boxes of dispense tips

Specifications

Cabinet Dimensions:	183 mm x 86 mm x 51 mm (7.22" W x 3.38" D x 2" H)
Weight:	1 Kg (2.2 Lbs)
Input AC (to power supply):	Universal Multi Voltage 100-240 VAC~ – 50/60 Hz
Output DC (from power supply):	24 VDC – 0.83 Amp maximum
Power Requirements:	24 VDC – 0.83 Amp maximum
DC Input Power Required:	8W-20W
Internal Voltage:	24 VDC
Footswitch:	
Voltage:	24 VDC
Current:	20mA
Cycle Initiate:	Foot Pedal, Finger Switch
Maximum Cycle Rate:	600 cycles per minute
Air Input Requirements:	7 bar (100 psi) maximum
Air Output:	0-7 bar (0-100 psi) Performus III 0-1 bar (0-15 psi) Performus IV dependent on user setting
Ambient Operating Conditions:	
Temperature:	5°C to 45°C (41°F-113°F)
Humidity:	85% RH at 30°C non-condensing
Height above sea level:	2000 meters maximum (6562 feet)
Approvals:	CE, CSA RoHS, WEEE & China RoHS Compliant

		Performus III	Performus IV
Dispense Time Display	Digital	✓	✓
Air Pressure Display	Analog		
	Digital	✓	✓
Vacuum Display	Digital		
Adjustability	Dispense time	✓	✓
	Air pressure	✓	✓
	Vacuum	✓	✓
Modes of Operation	Steady	✓	✓
	Timed	✓	✓
	Teach		
Time Range	0-99.9 seconds	✓	✓
Air Pressure Range	0-7 bar (0-100 psi)	✓	
	0-1 bar (0-15 psi)		✓
Input/Output Connection	5-24 VDC signal		
Universal Voltage	(100-220/240 volts)	✓	✓
Warranty	1 year		
	2 years	✓	✓

EFD®
A NORDSON COMPANY

For EFD sales and service in over 30 countries,
contact EFD or go to www.efd-inc.com/contact

EFD, Inc.
East Providence, RI USA
USA & Canada: 800-556-3484; +1-401-434-1680
info@efd-inc.com www.efd-inc.com

EFD International Inc.
Dunstable, Bedfordshire, UK
0800 585733 or +44 (0) 1582 666334
Ireland 00800 8272 9444
europe@efd-inc.com www.efd-inc.com

EFD, Inc., Asia
China: +86 (21) 5854 2345
china@efd-inc.com www.efd-inc.com/cn
Singapore: +65 6896 9630 sin-mal@efd-inc.com
The Wave Design is a trademark of Nordson Corporation.
© 2007 Nordson Corporation v100307